



Single inline swivel connector. Typically used on sloping guardrail. This fitting combines 1 x 173M & 173F. The swivels can travel approximately 85° from the horizontal in both directions. **THIS FITTING IS NOT DESIGNED TO WITHSTAND LATERAL LOADINGS. AN ENTIRE STRUCTURE SHOULD NOT BE BUILT ONLY USING SWIVEL FITTINGS, THIS WOULD BE UNSTABLE.**

PART CODE	MATERIAL	TUBE SIZE ϕ	A	B	C	FINISH
16173A	Malleable Cast Iron	26.9	53mm	38mm	39mm	Galvanised
16173B	Malleable Cast Iron	33.7	60mm	42mm	41mm	Galvanised
16173C	Malleable Cast Iron	42.4	63mm	47mm	44mm	Galvanised
16173D	Malleable Cast Iron	48.3	70mm	50mm	50mm	Galvanised
16173E	Malleable Cast Iron	60.3	95mm	60mm	70mm	Galvanised

DESCRIPTION: TubeClamp Single Swivel Combination						
	NAME	DATE	REVISION	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS		A3
DRAWN	TS	28/03/2022	A			
CHECKED				DO NOT SCALE DRAWING	SCALE:1:1	