

PRODUCT CODE: 2910

ANTI-SPLATTER FOR WELDING (W506)

DESCRIPTION

This product is silicone free, and is ideal for professional and DIY uses. This spray prevents corrosion, it protects from humidity and helps prevent spatter from adhering to surfaces.

ANTI-SPATTER FOR WELDING - A product made of film-forming synthetic polymers which, owing to their special characteristics, prevents spatter from adhering to surfaces. The film also prevents oxidation and corrosion by chemical agents. It is suitable for autogenous, electric and inert-gas welding. The compound is free of silicon substances.

TECHNICAL SPECIFICATIONS:

Quantity	400 ml
Confection	12 pz
Aspect	Tin-plate can, containing under pressure fluid
Colour	Light yellow
Odour	Characteristic of solvent
Drying Times	At 20° C 0,65 ÷ 0,85 g/ml
Flash point	0° C
Pressure a 20° C	3/5 bar



STORAGE

Before using: stock the product in a dry location. Do not store at temperatures below 0° C.

After use, keep containers closed. In the original package, the product can be stored for 24 months.

After the first usage: Store in a ventilated, dry location and away from heat sources. Keep out of reach of children.

Hazards Identification:

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, including the violation of many license. Before using, the users have to verify the suitability of the product for the specific use.

Whilst every effort has been made to ensure the accuracy of the information supplied. F.H. Brundle cannot be held responsible for any errors or omissions. This product must only be employed for its original intended use. Any other use is wrong and potentially dangerous. Installation must be carried out in full compliance with current regulations. F.H. Brundle cannot be held liable for any damages resulting from wrongful, erroneous or negligent use.