



F.H. BRUNDLE
SERVING THE TRADE SINCE 1889



NEW PRODUCTS



OVER 1500 NEW PRODUCTS IN STOCK

Steel Sections & More

Steel Sections - Galvanised (See Cat page 16)

Angle



Flat Bar



Square Bar



Round Bar



Aluminium Sections - Mill Finish (See Cat page 18)

Angle



Flat Bar




Square Bar



Round Bar



Sheet



Rectangular Box



Square Box



Round Tube



Stainless Steel Sections - Mill Finish (See Cat page 20)

Angle



Rectangular Box




Square Box



Round Tube



Sheet



Square Bar



Round Bar



See our website for quantity discounts.

Bright Bar Sections (See Cat page 12)

Flat Bar



Round Bar



GRP Profiles (See Cat page 22)

Round Tube



Square Box



Explore our entire range of steel sections & more from page 8.

ERW Steel Sections (See Cat page 13)



Create modern gate designs, using our new range of ERW tube and steel sections.

L Shaped Tube



Rectangular Tube




T Shaped Tube



40 x 10mm Tube



Convex Tube




T Sections



WPC Gate & Fence Infill Boards (See Cat page 63)

Also now stocked
in 3.6m lengths.



- Enhanced woodgrain effect surface
- UV resistant
- Available in 1820 & 3600mm lengths
- Stain and scratch resistant
- Co-extruded capping board
- Available in 4 colours
- Deflects unwanted noise
- Moisture resistant



Charcoal



Light
Grey



Teak



Walnut



Steel Sections & More

Adjustable Feet & Inserts (See Cat page 25)



Light Duty
Adjustable foot



Light Duty
Static adjuster




Medium Duty
Non-tilt adjuster



Heavy Duty
All steel adjuster

Now stocking a wide variety of adjustable feet!

Tube Connectors (See Cat page 26)



- Suitable for 25mm square tube
- No core or steel core option

- Ideal for freestanding structures
- Simple & easy to use


Tube Connector

2 Way Corner

3 Way Tee

3 Way Corner

Box Section



Discover the full range of fittings on page 26.

Castor Wheel - For Use With Galvanised Tube (See Cat page 27)

With Brake

Without Brake



Maximum load weight 100kg. To suit tube sizes Ø 26.9, 33.7, 42.4 & 48.3mm.

Cast your eyes on
the rest of the range.

Wrought Iron Components

Stainless Steel Laser Cut Numbers (See Cat page 155)




0 1 2 3
4 5 6 7
8 9


Stainless steel 100mm height, 1.5mm thick. With a 3M self adhesive backing, so no screwing or drilling is required.

Full range of laser cut letters & numbers on page 155.

Weldable Panels - Design Your Own (See Cat page 64)



Full Panel



Half panels also available.



Gate Hardware

Concealed 3D Hinges (See Cat page 174)



For aluminium profiles



For gates & square tube profiles



Maximum gate weight per pair 160kg. Sold as pair.

Gate Hardware

Soft Close Hinges (See Cat page 188)



Polaris Hinges are designed for a variety of installations from, retail pedestrian and security gates, to childcare and playground facility access. As well as balustrade and stairways gates and of course frameless glass pool fence gates, timber gates, aluminium gates and vinyl gates.

- Soft close mechanism
- Available in satin or PPC black

- Retro-fit to brick, glass, wood, metal & more
- Suitable for 8 - 12mm glass thickness

Soft Close Hinges

Sold in pairs. Stainless steel Grade 2205 Duplex.

Premium Latches

Sold as single. Stainless steel Grade 2205 Duplex.



Glass To
Glass



Glass To
Round Post



Glass To
Wall



Glass To
Glass 90°



Glass To Round
Post 180°



Glass To
Wall



Utility Hinge

Sold in pairs. Suitable for glass, metal and timber gates. Stainless steel Grade 2205 Duplex.



PowerClose Hinges (See Cat page 189)

Our PowerClose system helps overcome the most hard to close or electric strike lock gates, helping to complete a full gate/door closure. Additionally, when working with critical close situations or especially heavy or stubborn strike gates, multiple PowerClose units can be fitted to help ensure effective closing.



Sold in pairs. Stainless steel Grade 2205 Duplex.

Locinox Venus Motorised Gate Closer (See Cat page 195)



The Venus motorised gate closer is specifically designed for pedestrian gates up to 1.4m wide with a maximum gate weight of 100kg. Equipped with a reversible brushless motor rated at 150Nm, the Venus guarantees controlled closing in just 5 seconds.

- Wi-Fi connection for hands free access
- Automatically detects objects & obstructions
- Open angle up to 175 degrees
- Adjustable force & closing speed

Straight Arm Kit (Venus-S)



Cranked arm and 180° hinged arm versions available.

Supplied with Venus gate closer and straight arm connector.

Locinox Vera Wireless Access Control (See Cat page 212)



Vera is a battery-operated code lock that works perfectly with our range of insert locks. Even if you recently finished a project with an insert lock, the Vera can be added just as easily to existing installations.

- No mains power required. Battery pack included
- Easy programming of up to 100 user codes
- To be used with SFKU-V keep
- To be used with FORTY & FIFTY LOCK


Single-Sided




Double-Sided



Cantilever Bullet System (See Cat page 240)




These innovative mono-carriages are the easiest and fastest to install ever. The adjustable, precise, rapid installation mono-carriage, makes configuration easy.



Adjustable to 3 positions.

Gate Hardware

Cantilever Gate Kits (See Cat page 242)



- Maximum cladding weight 125kg
- Ideal for uneven road surfaces


- No groundwork or track required between gate opening
- Lower noise levels than traditional track and wheels

Kits Include:

- 1 x Gate frame
- 1 x kit - bolts & nuts
- 1 x roller
- 1 x end stop
- 2 x end caps
- 2 x 8 wheel support rollers
- 1 x tensioner
- 1 x roller guide
- 1 x roller guide bracket
- 1 x end stop
- 2 x tracks



Clad the gate frames with a material of your choice.




Straight out of the box ready to be installed.



Scan here for
installation guide.

Bi-Folding Twin Drive Gate Kits (See Cat page 246)



The Twin Drive bi-folding gate hardware kit is particularly useful in places where a traditional swinging gate has no space to operate. The installation does not require welding or complicated steps and materials.


Gate Kit - Suitable for left and right hand openings



- Quick & easy to install
- Max gate weight 110kg per leaf
- Max opening single leaf 3m & double leaf 6m
- Suitable for max 1.6m gate height
- Space-saving – offering vehicles full manoeuvrability
- 90 degree opening
- Trackless
- Perfect for gravel surfaces

Image shows box contents of a single leaf gate kit. Double leaf kits have 2 of everything pictured above.

Albatross Bi-Folding Gate Kits (See Cat page 247)



- Suitable for heavy duty gates up to 150kg per leaf
- Quick & easy to install
- Max opening 4 or 8m
- For use with arm or underground automation

Component List

Adjustable Bracket



Lower Geared Hinge With power transmission arm



Upper Geared Hinge



Box Section 40 x 40 x 3mm



Kits contain 1 x Albatross hinge no arm, 1 x Albatross hinge with arm, and 1 x Albatross movement system.

Gate Automation

e-Loop Wireless Vehicle Detection Systems (See Cat page 279)



Domestic e-Loop

Exit mode

The E-loop Mini is an exceptional wireless vehicle detection system that is perfectly suited for domestic house settings. With its compact design and easy installation you can seamlessly integrate this into any residential environment without disrupting the aesthetic appeal.

- Quick & easy installation
- Uses standard 1.5V AA Lithium batteries
- Small compact design
- Static load capacity 2500kg
- Range up to 50m
- High security 128-bit encryption



Commercial e-Loop

Presence mode

With a convenient presence mode, which intelligently keeps gates and barriers open for an extended duration when longer vehicles are in motion over the detection area. This advanced functionality enhances safety and efficiency by minimizing interruptions and reducing the risk of collisions, further solidifying its suitability for commercial environments.

- Quick & easy installation
- Dual sensor technology
- 10600 mA battery gives up to 6-10 years of battery life
- Made of high impact plastic
- Range up to 50m
- High security 128-bit encryption




Commercial Inground e-Loop

Presence mode

The flush unit provides durability and resistance to heavy loads, making it suitable for high-traffic areas such as busy parking lots or loading docks. With its unassuming presence and robust construction, the e-loop commercial is an ideal choice for businesses that prioritise both functionality and aesthetics.

- Recess into driveway
- Dual sensor technology
- 14500 mA battery gives up to 6-10 years of battery life
- Not affected by ground movement
- Range up to 50m
- High security 128-bit encryption



Welded Mesh - Pre-Galvanised (See Cat page 296)




3" x 1/2" x 8g Pre-Galvanised Panels

The panels are 2.515m wide, mesh sizes are 76.2 x 12.7mm, manufactured from 4mm wires and galvanised. Featuring a toe and finger proof mesh aperture, this system combines an anti-climb and anti-cut fence with excellent through visibility and resistance to vandalism.

See our full range of mesh from page 294.


Decking & Landscaping

Synergised™ Original Aluminium Deck Boards (See Cat page 340)




- A1 and A2fl-s1 fire rated
- Ideal for high rise concrete balconies & terraces
- Up to 50% cost saving when compared to other systems
- 100 micron Qualicoat™ premium powder coating
- Adjustable cradle and deck support system
- Joist spacing up to 800mm centres
- Low surface temperatures
- Long lasting and low maintenance
- Lightweight and easy to install


17mm Deck Boards - Anthracite. RAL 7016




30mm deck boards also available.




Double clip




Adjustable cradles



Deck joining plate



Corner brace



90°Joining bracket

Decking & Landscaping


Synergised™ Aluminium Balcony Boards (See Cat page 345)

- A1 and A2fl-s1 fire rated
- Quick & easy to install
- Non-slip design


- Compatible with a range of subframe and cradles
- Range of draining options available
- Lifespan of over 60 years

Balcony Board & Infill - Anthracite. RAL 7016

18mm Profile




25mm Profile



Cross Section Of An Installed Drainage System

Gutter Trim Application



Effective Water Drainage

The 25mm balcony board system is available with a full water management solution. This includes a drain channel which fits between the boards to carry the water away, and a gutter section which collects the water and is connected to the site drainage. The drain channel is also designed to create the perfect spacing between the boards to eliminate the need for measurements. The gutter profile is 30mm high and includes screw ports to enable fixing of end caps to close the section off.

Drainage Channel




Black RAL 9005

Gutter - Lower Section




Anthracite RAL 7016

Gutter - Trim



Anthracite RAL 7016

Gutter - End Cap



Anthracite RAL 7016

Straightcurve® (See Cat page 349)



Straightcurve® is the UK's only high-end modular steel landscaping range that is quick and easy to install using basic household tools. Pre-drilled and prepared for self-assembly, and specifically designed for ease of installation, this stylish range consists of modular garden edging, raised garden beds, and planter box systems.

- Effortlessly connect edges and strongly brace products for a stress-free design process
- Save time & money by eliminating custom fabrication and on-site welding
- Deliver beautiful, safe, and child-friendly designs that will delight your clients
- Use a family of high-quality steel landscaping products sharing quick-connect & easy install DNA

Garden Edging



With little to no fuss, simply fix lengths together and position in your garden for a professionally finished look.

Planters



With little to no fuss, simply fix panels together and place in your garden for a professionally finished look.

Raised Garden Beds




In varying styles and heights to suit your garden design.

Designed for DIY home gardeners. Loved by landscape professionals.

Straightcurve Flex

Best for smooth, flowing curves.



Straightcurve Rigid

Best for mostly straight or gently curving lines.



Straightcurve Zero-Flex

Best for perfectly straight, unmovable lines.



Ground Screws



DIY Range (See Cat page 356)

For customers who need the benefits of ground screw foundations, but for smaller scale projects with lighter loading requirements, we offer a high-quality range of 68mm diameter ground screws with lengths of up to 1200mm specifically designed for DIY installation.

- 100mm head
- Made from grade S235 mild steel

- Hot dipped galvanized to DIN EN ISO 1461
- For use with installation tool below





Installation Tool



Only for use with the DIY ground screws, not the Professional range.

3 x Ø 10 x 40mm curved slots



Professional range (See Cat page 357)



We now provide a range of ground 76mm diameter screws specifically designed for optimum performance, longevity and structural integrity. Our professional range of ground screws are made with higher quality steel than any other UK supplier.

- 200mm head (140mm head also available)
- Made from grade 345 mild steel

- Hot dipped galvanized to DIN EN ISO 1461
- Tool hire required for installation




3 x Ø 13 x 55mm curved slots




Open Steel Stair Treads (See Cat page 365)

TYPE 41/100mm



With perforated nosing

Cut Your Own Type 41/100mm




Cut stair tread to length required & weld-on the plate

Durbar Stair Treads (See Cat page 371)

Mild Steel Folded



Galvanised




Unbeatable prices!

Plates & Sheets

Aluminium Chequer Plate (p.373)




Mild Steel Durbar Sheet (p.371)



GRP Gratings

Grey Covered Top (p.375)



Waffle Boards (p.376)



Fixing Clips

'C' Joining Clip (p.376)



For joining GRP grating together

Flooring & Stair Treads

GRP Deck 250 Board (See Cat page 378)




The latest offering to our GRP flooring range is the Deck 250 Board. Supplied in a non-slip coated finish, its unique interlocking boards seamlessly connect, allowing the system to be fitted quickly and easily.

- Non-slip
- Nonconductive
- Fire retardant


- Corrosion resistant
- Walkways, pedestrian bridges and raised floors
- Ideal for step overs

Anti-Slip Decking Plank



With gritted top

Boards Screw Into Joist And Interlock



Handrailing & Balustrades

GRP Round Fitting Gates (See Cat page 422)

Single Gate



Supplied with hinges and latch.
Suitable for right or left hand opening.

Double Gate



Supplied with hinges, latch and kick plate.
Suitable for right or left hand opening.

End Post



GRP single and double gates are supplied with D&D toggle latch (as shown left).

For GRP posts & mesh infill panels see page 421.

GRP Ladder Kits (See Cat page 428)



Rise Size mm

2200 - 2650

2750 - 3200

3150 - 3600

3700 - 4150


4250 - 4700

4650 - 5100

5200 - 5650

5750 - 6200



This safe, simple modular design offering individual parts which bolt together, is flexible, easy to install and will solve virtually any access problem. An inexpensive, modular solution to permanent roof access installations and can be configured to suit any installation requirements.




Mezzirail® (See Cat page 399)

50mm Square Bolt-Down Mid Post

With no slot



To suit any Ø 33.7mm tube.
2.5mm thickness. BZP.



Tube

Folded Kick Plate



2mm thickness. BZP.




Tek Screw kick plate to side of post.

Handrailing & Balustrades

Tubular Raked Handrail Standards (See Cat page 388)

Galvanised to fit Ø 33.7, 42.4 & 48.3mm tube

38° Rake Post Weld-Fix




Permanently lower prices.

Full technical
specification
available online



Can be cut to size for use.


38° Rake Post Flat Base-Fix



12mm flat drilled base plate.
Ø 18mm holes for M16 bolts.




38° Rake Side-Fix



12mm flat drilled
base plate.
Ø 18mm holes for
M16 bolts.



38° Rake Post Raked Base-Fix




12mm drilled angled base plate.
Ø 18mm holes for M16 bolts.



Full Height Self-Closing Gates (p.390)

Galvanised to fit Ø 33.7, 42.4 & 48.3mm tube



With kick plate.

Handrail Bends (See Cat page 394)

Stair Return Bends



450mm centres, 38 degree
rake. 400mm legs.

More handrail
bends on
page 394.

Ramp Bends




38 degree rake. 450mm legs.

Top & Mid Rail Fixed & Adjustable Tube Clamp Posts (See Cat page 404)


Bolt-Down Posts

To suit any Ø 33.7mm tube



Concrete-In Posts


To suit any Ø 42.4 or 48.3mm tube



Make Your Own Gate (See Cat page 396)

To suit Ø 33.7, 42.4 & 48.3mm tube & fittings


Pre-Welded Self-Closing Gate Hinge Set




Tube Clamps (p.409)

Through Tube Wall Flange

Round Base



Square Base




To suit Ø 33.7mm, 42.4 or 48.3mm tube.


Handrailing & Balustrades

Bendy Steel - Stargard Flex (See Cat page 406)

Bend it like Beckham, without any tools or special skills required.




Bendy Steel has been designed with flexibility in mind and can easily be manipulated by hand to suit all sorts of bends and angles. Suitable for use with standard tube clamp fittings, you simply strip back the outer coating for a seamless connection. **Please note that Ø 42.4mm fittings contain Ø 33.7mm galvanised tube core with PVC sleeve, and Ø 50.0mm fittings contain Ø42.4mm galvanised tube core.**



Bendability!



Adjustable Handrail Section



Adjustable Handrail Return




Fixed Return Bend



Fixed 90° Section

Square Tube Clamps (See Cat page 417)




Fortitude™ Classic (See Cat page 440)

FORTITUDE™





Fixed Railing Panel

To give 1100mm high railings



Adjustable Raking panel

For stairs & slopes, up to 40°





Fortitude™ Timeless (See Cat page 442)




Pre-Drilled Posts For Glass Clamps

Glass Clamp Flat back



Supplied with bolts.



Handrailing & Balustrades


Fortitude™ Post & Rail (See Cat page 448)



If it's just a handrail option you require, then our simple to install post and rail system is the ideal solution. By using the 50mm posts and the handrail components from our capping system, you can create a basic, but stylish handrail solution - **See capping below.**

Bolt-Down Posts
50mm

Concrete-In Posts
50mm



Ground level

Versatile Capping Handrail System (See Cat page 498)




Can be fixed to the top of any 50mm square post.

Our 70 x 45mm capping profile is one of the most versatile handrailing systems on the market. Not only is it cost effective, but it's also quick and easy to install, with only a single screw needed to secure it to the post. Available in satin anodised, black gloss, or black sand, this handrail is suitable for any 50mm square post.


- Cost effective, quick & easy to install
- Secured by a single bolt through the handrail & into the post
- Connectors can be glued for ease of use
- Suitable for any 50mm square post



Using fixed components



Using Adjustable components



Adjustable Spigots (See Cat page 454)



- Adjustable up to 44 degrees
- For use with 12 - 17.5mm glass

Oval Spigot


No holes in glass needed



Adjustable up to 44°. Height to glass when packer fitted is 100mm. Designed for use with matching standard spigot when moving onto a flat surface.

Square Spigot

No holes in glass needed



Adjustable up to 44°. Height to glass when packer fitted is 100mm. Designed for use with matching standard spigot when moving onto a flat surface.


- Tested to BS6180
- Available in satin polish finish

Side-Fix Spigot


No holes in glass needed



Adjustable up to 44°. Height to glass when packer fitted is 61mm. Designed for use with matching standard spigot when moving onto a flat surface.



POSlone System (See Cat page 472)





POSlone has all the benefits of POSiglaze but can be installed and adjusted from one side. This channel is ideal for domestic and light commercial installations. Garden patios, stair bannisters, balconies and windbreaks are just a few installation ideas.

- Fast install from one side, and fully adjustable
- Lightweight and extremely strong

Install & adjust from one side.

Base-Fix



Channel fixing holes are Ø 15mm at 200mm centres to suit a Ø 12mm bolt.

- Suitable for domestic and commercial applications
- Available in silver anodised brush or black finish

Handrailing & Balustrades

Pro-Railing® Side-Fix Posts - Satin Polish (See Cat page 513)




Internal Corner Post

Designed to give 1100mm to top of handrail.

External Corner Post

Mid Post



Posts supplied with fascia brackets and end cap for the base of the post.

Finish floor level

Saddles not included.



For our full range of tube see page 533.

See handrail fittings for the top of your post on page 535.



Stainless Glass Clamps (See Cat page 541) - Now available in black.

Round Back



180° Double



90° Double



Check out the prices!
From just
£1.50 each.

Stiffeners (See Cat page 546) - Aluminium Satin & PPC Black. To suit 12 - 21.52mm glass.


90° Bracket



180° Bracket



Wall Bracket




Pro-Railing® Stainless Steel Posts - Black Finish (See Cat page 518)



Timeless - With Handrail

Designed to give 1100mm to top of handrail.
Saddles not included.

Tube



Handrail Saddles



For tube and saddles
see page 540.


Contemplation - Without Handrail

Designed to give 1100mm to top of glass panel.
Post cap not included.

End

Mid

Corner



Glass Panels



10mm glass panels
can be found on
page 509.

Post Cap



To be used with
bolt-down posts.
See page 541.

Handrailing & Balustrades

Marano® Aluminium Handrailing (See Cat page 500)




Marano is an innovative railing system designed to be fully modular. The pre-assembled aluminium 50mm square posts are ready to install. The system can be fully fitted using basic equipment and comes fully engineered to meet the requirements of most applications.

- Fully assembled posts
- Aluminium satin anodised & PPC black finish
- To suit 10mm glass
- Suitable for indoor & outdoor installations

Bolt-Down Posts


End



Mid




Corner




Side-Fix Posts

End




Mid



All posts can be used with or without handrail.

With Handrail



Without Handrail



Handrail Components & Accessories



View our full range of handrail components and accessories on pages 497 and 501.


Marano® Integrated (See Cat page 589) Wave



MARANO®


Board Size

L: 1825mm x H: 120mm x T: 20.6mm




Basalt Grey Black Sand Mill Finish

Ridged



Board Size

L: 1825mm x H: 100mm x T: 20.6mm



Basalt Grey Black Sand Mill Finish

Horizontal LED Rail Set

For use as top or bottom rail




Horizontal LED



Waterproof Driver



PVC Laser Cut Screens (See Cat page 600)



Woodland



Palm



Sunburst



Dahlia



Ivy



Prism



Screens available in various sizes see page 600.

Marano® Blade (See Cat page 610)

MARANO®

Introducing the Blade Series: the ultimate modern style for residential properties. Our Blade range offers innovative vertical bar fencing designs, crafted from high-quality aluminium with a signature black sand powder coating for superior durability and a sleek finish.

Blade 90



Bars set at a 90° angle to the rail

Plan view of in-line installation



Plan view of face-fix installation



Blade 45



Bars set at a 45° angle to the rail

Plan view of in-line installation



Plan view of face-fix installation



Vertical Slat Panels



Slats are set horizontal to the rail

Plan view of in-line installation




Plan view of face-fix installation



Panels can be fixed to the inside of the post, using a railing bracket, or the outside of the post, using an angle bracket.

Prefabricated panels ready for easy installation.




Fortitude™ Adjustable Sphere Top Railings (See Cat page 630)



Adjustable Panel

Can create rakes in excess of 45°



Angle Bracket



Horizontal Bracket



Adjustable Vertical Bracket



Brackets are supplied as pack of 4 with screws. For use with sphere top panels and post.


Adjust on site to the gradient required.

Fortitude™ Smooth Top (See Cat page 639)




- 1.2m fence height
- Full & half width panels
- 12mm square bar
- Single & double leaf gates
- 50mm square concrete-in posts
- Mild steel, galvanised or PPC black RAL 9005

Full Panel



Also available in half panels.

Concrete-In Posts



Fencing, Gates & Security



Fortitude™ Estate Fencing (See Cat page 615)



This type of fencing and gates have become a popular solution with house builders in residential developments. Our estate fencing is supplied in ready made panels, making it a quick and economical fencing solution. Also ideal for use as continuous boundary fence in parkland, paddocks and estates.

Now available in uncoated mild steel, to weather once installed.

Pedestrian Barrier (See Cat page 650)



Size 2262 x 1100 x 452 mm

Rebound 868 (See Cat page 662)



Manufactured from 6mm diameter vertical wires set between twin 8mm diameter horizontal wires, absorbs the impact of sport balls and returns them back into play. This system is available with full height clamp bar fixing, supplied with security fixing. The panels are 2.506m wide and have twin wires to give increased strength and rigidity. Mesh size is 50 x 200mm (50 x 66mm for 1.2m high rebound section). Metre runs include intermediate posts and clamp bars.

Available in PPC Black.

'W' Section Palisade - Network Rail Spec (See Cat page 679)



Network Rail compliant Palisade gates available on page 683.

Palisade Gates (See Cat page 681)



- Galvanised
- Gates open inwards & outwards 100°
- Triple pointed 'D' 3mm or 'W' 2mm thick pales
- Supplied with adjustable gate eyes and drop bars
- Padlockable slide latch
- 6m gates now available

**Galvanised
Pales**



'D' Section



'W' Section

Meshmaster™ 656 Gates (See Cat page 664)



- Galvanised & polyester powder coated green or black
- Gates open inwards & outwards 100°
- Supplied with adjustable gate eyes and drop bars
- Padlockable slide latch

6m gates now available.

Meshmaster™ 358 Gates (See Cat page 670)



- Galvanised & polyester powder coated green or black
- Gates open inwards 180°
- Supplied with adjustable gate eyes and drop bars
- Padlockable slide latch
- Front mounted mesh with clamp bars
- Fitted with tamper proof fixings

6m gates now available.

Bollards (p.700)

Bolt-Down or Concrete-In



Column Protection (p.698)

Bolt-Down Post

760mm high



Plan View



Comes with 4 x 16 x 125mm bolts for fixing beams to the post.



F.H. BRUNDLE

SERVING THE TRADE SINCE 1889



Scan the QR code to find out more about what we do, or you can view our video at www.fhbrundle.co.uk or on YouTube.



PLAY



Distribution Hub

Wellington Road
Burton-upon-Trent
Staffordshire
DA13 2AA

Tel: 01283 743 010

South & West

502 Millbrook Road
Third Avenue
Millbrook
Southampton
Hants SO15 0JX

Tel: 023 8070 3333

Fax: 023 8070 5555

southampton@brundle.com

London & South East

24 - 36 Lamson Road
Ferry Lane North
Rainham
Essex
RM13 9YY

Tel: 01708 25 35 45

Fax: 01708 25 35 50

sales@brundle.com

East Midlands

Condor Road
Quarry Hill Ind. Est
Ilkeston
Derbyshire
DE7 4RE

Tel: 0115 930 2070

Fax: 0115 951 2455

ilkeston@brundle.com

West Midlands

81-82 Middlemore Ind. Est
Middlemore Road
Smethwick
Birmingham
B66 2EP

Tel: 0121 565 8282

Fax: 0121 565 8292

birmingham@brundle.com

North West

Unit B
Spectrum 23
Sankley Valley Ind. Est
Newton-le-Willows
WA12 8DN

Tel: 01942 86 88 88

Fax: 01942 86 88 99

haydock@brundle.com

Scotland

Dunivaig Road
Queenslie Ind. Est
Queenslie
Glasgow
G33 4TP

Tel: 0141 773 6699

Fax: 0141 773 6633

glasgow@brundle.com

South Wales

Alexandra Ind. Est.
Wentloog Rd
Rumney
Cardiff
CF3 1EY

Tel: 029 2280 1180

cardiff@brundle.com

Errors and omissions excepted. Whilst every effort has been made to ensure the accuracy of the information supplied, F.H.Brundle cannot be held responsible for any errors or omissions.